

Lo Torque Hole Openers

Available with Milled Tooth or TCI Cutters



Benefits and Features

Sharewell now offers Lo Torque Hole Opener Cutters to match the formation hardness of your bore. The Lo Torque Tungsten Carbide Cutter types now range from medium to extremely hard rock formations. Close attention to insert material composition of gage, inner row and base areas of the cutters optimizes their performance in the wide range of rock conditions encountered in horizontal drilling.

- Cantilevered Design for Less Drag
- Single Body for Multiple Hole Sizes
- Sale or Rental Body Options
- Field Interchangeable Cutters
- Custom Design with More Cutters on Larger Hole Sizes

Lo Torque Hole Opener Specifications

Body Size	Min Pilot Hole	# of Cutters	Body Weight (lbs.)	Length (in.)	Connections	Opening Range				
						A	B	C	D	E
LT2	2.5"	3	16	24"	2 IF B x P	6"				
LT4	4.5"	3	160	37.5"	2 7/8 IF B x P	8"	10"	12"		
LT6	6.5"	3	304	44"	3 1/2 IF B x P	12"	14"	16"		
LT8	8.5"	3	628	48.5"	4 1/2 IF B x P	16"	18"	20"	22"	24"
LT16	16.5"	3	1,194	48.5"	7 5/8 REG B x P	24"	26"	28"	30"	32"
LT16-4	16.5"	4	1,252	48.5"	7 5/8 REG B x P	24"	26"	28"	30"	32"

MANUFACTURED EXCLUSIVELY FOR:

