

DRILL LUBE **HDD**

PRODUCT DESCRIPTION

Drill-Lube HDD is an engineered blend of environmentally friendly lubricants designed to help you drill faster and pull pipe easier.

Through rigorous lab and field testing, *Drill-Lube HDD* has been formulated to vastly reduce rotational torque and drag while requiring less product usage than competitors. In addition, Drill-Lube HDD's affinity for metal coats all of the drill rods and bits which can reduce wear and extend the life of the tools.

Typical application ranges depend on each company's specific drilling program. DrillChem partners with operators to create a custom-tailored application to help drive efficiency and performance.

APPLICATION OVERVIEW:

Crossing Interval	1,000 gal Mud	2,000 gal Mud
Pilot Hole	2.5 gal (0.25%)	5 gal (0.25%)
1 st Cut	5 gal (0.50%)	10 gal (0.5%)
2 nd Cut	7.5 gal (0.75%)	15 gal (0.75%)
3 rd Cut	10 gal (1%)	20 gal (1%)
Final Pull	15 gal (1.5%)	30 gal (1.5%)

PRODUCT ADVANTAGES

- Highest potency lubricant on the market.
- Utilize significantly less lubricant for better results.
- Compatible with all water-based fluid systems.
- Consistently outperforms competitors in lab testing as well as the field.

PHYSICAL PROPERTIES

- Appearance: Light Tan
- Bulk Density: 1.85 SG

PACKAGING

- Drill-Lube HDD comes in Drums, 275-gallon or 330-gallon poly totes

Houston, Texas | Lafayette, Louisiana | Elk City, Oklahoma
Williston, North Dakota | Midland, Texas | Corpus Christi, Texas



641.629.1528 | drillchem.com