

# DUO-VIS

*DUO-VIS\* xanthan gum is a dispersible, non-clarified, high-molecular-weight biopolymer used for increasing viscosity in water-base systems. Small quantities provide viscosity and weight material suspension for all water-base mud systems. DUO-VIS biopolymer has the unique ability to produce a fluid that is highly shear-thinning and thixotropic.*

## **Typical Physical Properties**

Physical appearance.....	Cream-to-tan powder
Specific gravity .....	1.5
Bulk density .....	50 lb/ft <sup>3</sup> (800 kg/m <sup>3</sup> )

## **Applications**

The primary function of DUO-VIS biopolymer is to increase viscosity for cuttings transport and suspension. It performs effectively in all water-base fluids, from highly weighted to low-solids systems. This includes freshwater, seawater, salt and heavy-brine systems.

DUO-VIS biopolymer works to provide an optimized rheological profile with elevated low-shear-rate-viscosity and highly shear-thinning characteristics with low "n" values. These characteristics frequently result in fluids with inverted flow properties, *i.e.*, the yield point being greater than the plastic viscosity. Shear-thinning fluids have low effective viscosities at the high shear rates encountered inside the drillstring and at the bit. This low effective viscosity for minimal pressure losses and standpipe pressures allows optimized hydraulics and maximized rates of penetration. Conversely, at the low shear rates experienced in the annulus, DUO-VIS biopolymer enables the fluid to have a high effective viscosity for adequately cleaning the well and suspending cuttings.

DUO-VIS biopolymer should be added slowly through the hopper to prevent lumping and minimize waste. It should be added at the rate of approximately one 25-lb sack every seven minutes. The time required for the product to yield its ultimate viscosity depends on salinity, temperature and shear.

The amount of DUO-VIS biopolymer required depends upon the desired viscosity. Normal concentrations range from 0.25 to 2 lb/bbl (0.71 to 5.7 kg/m<sup>3</sup>) for most mud systems. Special fluids and difficult hole-cleaning conditions can require higher concentrations, up to 4 lb/bbl (11.4 kg/m<sup>3</sup>).

The addition of salt, an antioxidant and thermal stabilizers improve temperature stability in fluids from 250 to >280°F (121 to >138°C). Specially formulated systems have been used at temperatures of 400°F (204°C). DUO-VIS biopolymer is subject to bacterial degradation, and treatments with a biocide are recommended to prevent fermentation.



## ***Advantages***

- Highly effective viscosifier; small treatments produce significant results
- Shear-thinning rheological profile for improved hydraulics
- Minimum frictional pressure losses for additional hydraulic horsepower at the bit and low, high shear-rate viscosity for maximum penetration rates
- Viscous laminar flow in the annulus for improved wellbore stability with maximum hole-cleaning and suspension capacity
- Mixes easily

## ***Limitations***

- Trivalent ions such as chromium and iron can cause biopolymer precipitation and loss of viscosity or crosslinking
- Not tolerant of high-pH or high-calcium-ion conditions
- DUO-VIS systems should be pretreated with either sodium bicarbonate or SAPP and possibly citric acid prior to drilling cement
- Subject to bacterial degradation, a biocide should be used to prevent fermentation
- Slightly anionic nature of DUO-VIS biopolymer requires special mixing procedures when mixed with cationic materials

## ***Toxicity and Handling***

Bioassay information is available upon request.

Handle as an industrial chemical, wearing protective equipment and observing the precautions described in the Material Safety Data Sheet (MSDS).

## ***Packaging and Storage***

DUO-VIS biopolymer is packaged in 25-lb (11.3-kg) or 50-lb (22.7-kg), plastic-lined, multi-wall, paper sacks.

Store at room temperature in a dry, well-ventilated area. Keep in original container. Keep container closed. Store away from incompatibles.

This document is supplied solely for informational purposes and M-I SWACO makes no guarantees or warranties, either expressed or implied, with respect to the accuracy and use of this data. All product warranties and guarantees shall be governed by the Standard Terms of Sale. Nothing in this document is legal advice or is a substitute for competent legal advice.

